

ConTEXt

title : ConTEXt User Module
subtitle : Framework for Letters
author : Wolfgang Schuster
date : April 21, 2008

Constants and Variables

```

1 \writestatus{loading}{Context User Module / Framework for Letters}
2 \unprotect

I use a few extra constants and variables in my module.

3 \startconstants      all
4
5   graphic: graphic
6   head: head
7   foot: foot
8   backaddress: backaddress
9   topmark: topmark
10  botmark: botmark
11  cutmark: cutmark
12  endmark: endmark
13  usermark: usermark
14  foldmark: foldmark
15  extension: extension
16  interface: interface
17  backgroundimage: backgroundimage
18  whitespace: whitespace
19  optimize: optimize
20 \stopconstants

21 \startvariables      all
22
23  letter: letter
24  secondpage: secondpage
25  backaddress: backaddress
26  foot: foot
27  topmark: topmark
28  botmark: botmark
29  cutmark: cutmark
30  endmark: endmark
31  reference: reference
32  option: option
33  address: address
34  foldmark: foldmark
35  usermark: usermark
36  opening: opening
37  closing: closing
38  layer: layer
39  letternext: letternext
40  lettermain: lettermain
41  special: special
42  notation: notation
43  inside: inside
44 \stopvariables

```

Before we start the real module let us introduce two namespaces for the style and content setup commands.

```
7 \def\????ld{0000ld} % LetterData
  \def\????ls{0000ls} % LetterStyle
  \def\????lv{0000lv} % LetterValue

8 \startmodule[letter]

9 \setupmodule
  [\c!style=,           % default letter style
   \c!extension=,        % default letter extension
   \c!interface=default] % default letter interface
```

Setup commands

\setuplett... The layout for the first page could be set with the `firstpage` key and the layout for the second and all following pages with the `secondpage` key. You could use any key and value from \setuplayout to set your own letter layout.

```
\setupletterstyle [...1,...] [...,.2,...]
1   firstpage  secondpage
2   inherits from \setuplayout
```

The header and footer texts for the letter is set with the `header` and `footer` keys, the text itself I written as argument as one of the three keys. The command itself has no option to use different texts for odd and even pages (if you really want this in a letter) but you could solve this with the macro \doifoddpageelse, I will give you a short example below.

```
\setupletterstyle [...1,...] [...,.2,...]
1   header  footer
2   lefttext    = TEXT
      middletext = TEXT
      righttext   = TEXT
```

This setups could produce sometimes a unwanted result is you use a doublesided layout, because the values for `lefttext` and `righttext` change on odd and even pages their position, e.g. `righttext` will always go to the outer margin and `lefttext` to the inner margin. Let's you want the pagenumber always on the right side you could use the following code, you could adapt it to your own needs without problems.

```
\setupletterstyle
[header]
[lefttext=\doifoddpageelse\donothing\pagenumber,
 righttext=\doifoddpageelse\pagenumber\donothing]

10 \def\setupletterstyle
     {\dotripleempty\dosetupletterstyle}

11 \def\dosetupletterstyle[#1][#2][#3]%
     {\ifthirdargument
        \dodosetupletterstyle[#1][#2][#3]%
     \else\ifsecondargument
        \dodosetupletterstyle[#1][#2][]%
     \else
        \dodosetupletterstyle[\v!option][#1][]%
     \fi\fi}

12 \def\dodosetupletterstyle[#1][#2][#3]%
     {\processallactionsinset
      [#1]
      [\v!firstpage=>{\definelayout[\v!letter\v!firstpage][#2]}, 
       \v!secondpage=>{\definelayout[\v!letter\v!secondpage][#2]}, 
       \v!header=>{\dosetupletterheader[#2][#3]}],
```

```
\v!footer=>{\dosetupletterfooter[#2][#3]},  

\v!option=>{\getparameters[\????ls\v!option][#2]},  

\v!foldmark=>{\dodododosetupletterstyle[\v!topmark,\v!botmark,\v!cutmark][#2][#3]},  

\s!unknown=>{\dodododosetupletterstyle[#1][#2][#3]}}
```

Setup of the layers and their frames.

```
13 \def\dodododosetupletterstyle[#1][#2][#3]%
  {\def\dododododosetupletterstyle##1%
   {\doifelsenothing{##3}
    {\ExpandSecondAfter\doifinsetelse{##1}\letter!list!sections
     {\dododododosetupletterstyle[##1][\v!option][#2]}
     {\dododododosetupletterstyle[##1][\v!layer,\v!frame,\v!option][#2]}}
    {\dododododosetupletterstyle[##1][#2][#3]}}
   \processcommacommand[#1]\dodododosetupletterstyle}

14 \def\dodododododosetupletterstyle[#1][#2][#3]%
  {\def\dodododododosetupletterstyle##1%
   {\processaction
    [##1]
    [\v!layer=>{\dodododododosetupletterstyle[#1][\v!layer\v!a,\v!layer\v!b][#3]},
     \v!layer\v!a=>{\setupplayer[#1][#3]},
     \v!layer\v!b=>{\getparameters[\????ls#1\v!layer][#3]},
     \v!frame=>{\getparameters[\????ls#1\v!frame][#3]},
     \v!option=>{\getparameters[\????ls#1][#3]},
     \s!unknown=>{\getparameters[\????ls#1##1][#3]}]
   \processcommalist[#2]\dodododododosetupletterstyle}}
```

Setup for the header and footer texts.

```
15 \newtoks\letter!toks!header
\newtoks\letter!toks!footer

16 \def\dosetupletterheader[#1][#2]%
  {\letter!toks!header\emptytoks
   \doifelsenothing{#2}
   {\letter!toks!header{\setupheader[\v!text][#1]}}
   {\letter!toks!header{\setupheader[#1][#2]}}}

17 \def\dosetupletterfooter[#1][#2]%
  {\letter!toks!footer\emptytoks
   \doifelsenothing{#1}
   {\letter!toks!footer{\setupfooter[\v!text][#1]}}
   {\letter!toks!footer{\setupfooter[#1][#2]}}}
```

`\setupletter` The `\setupletter` macro could be used from a interface, I define only the macro and nothing else. You could also redefine the macro later because it is not used from the raw interface.

```
18 \def\setupletter
  {\dodoubleempty\dosetupletter}

19 \def\dosetupletter[#1][#2]%
  {\ifsecondargument
   \dodosetupletter[#1][#2]%
  \else\iffirstargument
```

```

    \dododotupletter[\v!option] [#1]%
\fi\fi}

20 \def\dododotupletter[#1] [#2]%
{\def\dododotupletter##1%
{\getparameters[\????ld##1] [#2]}%
\processcommalist[#1]\dododotupletter}

```

A few extra macros to test for content of the letter values, don't rely on them at the moment because they could change or I will remove, rename, rewrite etc. them.

```

21 \def\doiflettervalue#1#2%
{\doiftextelse{\lettervalue{#1}{#2}}
 \firstofoneargument
 \gobbleoneargument}

22 \def\doifelselettervalue#1#2%
{\doiftextelse{\lettervalue{#1}{#2}}
 \firstoftwoarguments
 \secondoftwoarguments}

```


Interface, Style and Extension files

\useletter..
 \useletter..
 \useletter..

This module provides different types of files beside the main module.
 Two of them could be used by the user while the third is only used in this file but you're free to use but you should really now what you do.

Each of the files has it's own file extension, you have to use if you want to create such a file, this has the advantage to use the same name for a collection of macros.

```
23 \def\letter!suffix!style    {nls}
     \def\letter!suffix!extension{nle}
     \def\letter!suffix!interface{nli}
```

Let us begin now to talk about the different types of files.

letter interface

The letter interface provides the connection between the user and the inner macros, it is possible to write a letter without a interface but you will loose many of the nice features. The features itself are defined within the interface and try to help the user to write a letter in a simpler than the raw interface.

I want to show you the difference between the default interface and the raw backend with a simple example, just a opening, the content and a closing text.

The example with the default interface looks like:

```
\startletter
  [opening=Hello User,
   closing=Good luck with your own interface]
I will show you how you could write a letter with my letter module
and the difference between the default and the raw interface. The raw
interface is should be only used by a high level interface and not the
user but you're free to do it.
\stopletter
```

The same example with the raw interface looks like:

```
\startsetups[letter:opening]
Hello User
\stopsetups

\startsetups[letter:content]
I will show you how you could write a letter with my letter module
and the difference between the default and the raw interface. The raw
interface is should be only used by a high level interface and not the
user but you're free to do it.
\stopsetups

\startsetups[letter:closing]
Good luck with your own interface
\stopsetups
```

The interface itself is loaded with the `\useletterinterface` command but you could also use the optional argument for `\usemodule` to load it. The first is only used in this file but it makes sense to use it also in a wrapper file for your own interface.

```

\useletterinterface [...,*,...]

*   IDENTIFIER

24 \def\useletterinterface
    {\dosingleargument\douseletterinterface}

25 \def\douseletterinterface[#1]%
    {\def\dodouseletterinterface##1%
     {\readfile{##1.\letter!suffix!interface}\donothing\donothing}%
      \processcommalist[#1]\douseletterinterface}

```

letter extension

The second filetype this module supports are letterextensions, you could use it to save macros and other values you want to use in many without the need to put it always in the real letter.

A few reasons for a letterextension file are:

- The letter head from your company,
- your own macro for the reference line,
- labels you need in different files (see `label.nle`),
- ...

The syntax to load a letterextension file is the same as for a interface and you could also argument for `\usemodule`.

```

\useletterextension [...,*,...]

*   IDENTIFIER

26 \def\useletterextension
    {\dosingleargument\douseletterextension}

27 \def\douseletterextension[#1]%
    {\def\dodouseletterextension##1%
     {\readfile{##1.\letter!suffix!extension}\donothing\donothing}%
      \processcommalist[#1]\douseletterextension}

```

letter styles

After I mentioned above how to load a interface and extension I will now come to the most important extension for the module.

Letter styles are used to change the layout of the letter, set the values for layers and enable and disable common options. Although it is possible to do all these things in the letter itself it is better to save often used settings in a extra file you could load on demand and share between your letters.

You could load a style file in the same way as the other to files, the first is `\useletterstyle` and the second the optional argument for `\usemodule`.

```

\useletterstyle [...,*...]
*   IDENTIFIER

28 \def\useletterstyle
    {\dosingleargument\douseletterstyle}

29 \def\douseletterstyle[#1]%
  {\def\dodouseletterstyle##1%
   {\readfile{##1.\letter!suffix!style}\donothing\donothing}%
   \processcommalist[#1]\dodouseletterstyle}

```

`\letterstyle..` `\lettervalue` The two commands `\letterstylevalue` and `\lettervalue` could be used to access the values for the keys used in the letterstyle settings and the letter values for information.

The rest of module contains only internal macros and other settings, you don't need them as a normal user but you look at the default.

```

30 \def\letterstylevalue#1#2%
  {\csname\????ls#1#2\endcsname}

31 \def\lettervalue#1#2%
  {\csname\????ld#1#2\endcsname}

32 \def\letter!list!marking
  {\v!topmark,\v!botmark,\v!cutmark,\v!endmark,\v!usermark}

33 \def\dododefinelayer[#1]%
  {\ifelse{#1}{\v!foldmark}
   {\def\dodododefinelayer##1{\dododefinelayer[##1]}%
    \processcommacommand[\letter!list!marking]\dodododefinelayer}%
   {\dododefinelayer[#1]}}

34 \def\dododefinelayer[#1]%
  {\setvalue{\????ls\v!option#1}{\v!yes}%
   \presetlocalframed[\????ls#1\v!frame]%
   \definelayer
    [#1]
    [\c!width=\paperwidth,
     \c!height=\paperheight]%
   \setupletterstyle
    [#1][\v!option]
    [\c!symbol=,
     \c!offset=\zeropoint,
     \c!leftmargin=\zeropoint,
     \c!rightmargin=\zeropoint]%
   \setupletterstyle
    [#1][\v!frame]
    [\c!frame=\v!off,
     \c!align=\v!right,
     \c!offset=\zeropoint,

```

```

    \c!strut=\v!yes]%
\setupletterstyle
[#1][\v!layer]
[\c!state=\v!start,
 \c!offset=\zeropoint,
 \c!preset=\v!left\v!top]

35 \def\dosetletterlayer[#1]%
{\doifinsetelse{#1}{\v!topmark,\v!botmark,\v!cutmark,\v!endmark,\v!usermark}
 {\doifelsenothing{\letterstylevalue{#1}\c!symbol}
  {\dodosetletterlayer[#1][\setup{letter:#1}]}
  {\dodosetletterlayer[#1][\letterstylevalue{#1}\c!symbol]}}
 {\dodosetletterlayer[#1][\setup{letter:#1}]))

36 \def\dodosetletterlayer[#1][#2]%
{\setlayer[#1]
 {\localframed[\????ls#1\v!frame]
  {\doadaptleftskip {\letterstylevalue{#1}\c!leftmargin}%
   \doadaptrightskip{\letterstylevalue{#1}\c!rightmargin}%
   \doattributes{\????ls#1\c!style\c!color{#2}}}}}

37 \let\letter!list!sections\empty

38 \def\dodefinelettersection[#1]%
{\appendtocommalist{#1}\letter!list!sections
\setupletterstyle
[#1]
[\v!option]
[\c!before=,
 \c!after=,
 \c!align=,
 \c!leftmargin=\zeropoint,
 \c!rightmargin=\zeropoint,
 \c!style=,
 \c!color=]}

39 \def\dosetlettersection[#1]%
{\begingroup
 \edef\@lettersection{#1}%
\doifelsenothing{\letterstylevalue\@lettersection\c!before}
 \endgraf
 {\letterstylevalue\@lettersection\c!before}%
\doadaptleftskip {\letterstylevalue\@lettersection\c!leftmargin}%
\doadaptrightskip{\letterstylevalue\@lettersection\c!rightmargin}%
\doifsomething{\letterstylevalue\@lettersection\c!align}
 {\setupalign[\letterstylevalue\@lettersection\c!align]}%
\dostartattributes{\????ls#1\c!style\c!color\empty
 \setup{letter:#1}%
\dostopattributes
\doifelsenothing{\letterstylevalue\@lettersection\c!after}
 \endgraf
 {\letterstylevalue\@lettersection\c!after}%
\endgroup}

```

Placement of the content

Enable the layouts for the first and second page.

```
40 \startsetups[letter:layout]
41   \setuplayout[\v!letter\v!firstpage]
42   \appendtoks\setuplayout[\v!letter\v!secondpage]\to\everyaftershipout
43 \stopsetups
```

Header for the first page, you could use it to place the logo from your company or your own address and name.

```
44 \dodefineletterlayer[\v!head]
45 \startsetups[letter:place:head]
46   \dosetletterlayer[\v!head]
47 \stopsetups

Address

48 \dodefineletterlayer[\v!address]
49 \startsetups[letter:place:address]
50   \dosetletterlayer[\v!address]
51 \stopsetups
```

Could be used to place a backaddress above the normal address.

```
52 \dodefineletterlayer[\v!backaddress]
53 \startsetups[letter:place:backaddress]
54   \dosetletterlayer[\v!backaddress]
55 \stopsetups
```

Reference line

```
56 \dodefineletterlayer[\v!reference]
57 \startsetups[letter:place:reference]
58   \dosetletterlayer[\v!reference]
59 \stopsetups
```

Footer block, you could use it to place information about your company but take care set `repeat=yes` if you want to place it on every page, you should disable the footer for the second and following pages inb this case.

```

60 \dodefinelayerlayer[\v!foot]
61 \startsetups[letter:place:foot]
62   \dosetletterlayer[\v!foot]
63 \stopsetups

```

Two additional layers from Hans Hagen's own letter module, it provide for users who used `m-letter.tex` and want to switch to my module.

I need they also for my pragma letter interface.

```

64 \dodefinelayerlayer[\v!lettermain]
65 \startsetups[letter:place:lettermain]
66   \dosetletterlayer[\v!lettermain]
67 \stopsetups
68 \dodefinelayerlayer[\v!letternext]
69 \startsetups[letter:place:letternext]
70   \dosetletterlayer[\v!letternext]
71 \stopsetups

```

Letterhead, american only

```

72 \dodefinelayersection[\v!letter\v!head]
73 \startsetups[letter:place:\v!letter\v!head]
74   \dosetlettersection[\v!letter\v!head]
75 \stopsetups

```

Date Line, american only

```

76 \dodefinelayersection[\v!date\v!line]
77 \startsetups[letter:place:\v!date\v!line]
78   \dosetlettersection[\v!date\v!line]
79 \stopsetups

```

Reference Line, american only

```

80 \dodefinelayersection[\v!reference\v!line]
81 \startsetups[letter:place:\v!reference\v!line]
82   \dosetlettersection[\v!reference\v!line]

```

```

83 \stopsetups
    Special Notation, american only
84 \dodefinelettersection[\v!special\v!notation]
85 \startsetups[letter:place:\v!special\v!notation]
86   \dosetlettersection[\v!special\v!notation]
87 \stopsetups
    Inside Address, american only
88 \dodefinelettersection[\v!inside\v!address]
89 \startsetups[letter:place:\v!inside\v!address]
90   \dosetlettersection[\v!inside\v!address]
91 \stopsetups
    Title
92 \dodefinelettersection[\v!title]
93 \startsetups[letter:place:\v!title]
94   \dosetlettersection[\v!title]
95 \stopsetups
    Subject
96 \dodefinelettersection[\v!subject]
97 \startsetups[letter:place:\v!subject]
98   \dosetlettersection[\v!subject]
99 \stopsetups
    Opening
100 \dodefinelettersection[\v!opening]
101 \startsetups[letter:place:\v!opening]
102   \dosetlettersection[\v!opening]
103 \stopsetups
    Letter content
104 \dodefinelettersection[\v!content]
105 \startsetups[letter:place:\v!content]

```

```

106 \begingroup
107 \doif{something}{\@c@l{optionindenting}}{\setup{indenting[\@c@l{optionindenting}]}}
108 \dosetlettersection[\v!content]
109 \endgroup
110 \stopsetups

    Closing

111 \dodefinelettersection[\v!closing]
112 \startsetups[letter:place:\v!closing]
113 \dosetlettersection[\v!closing]
114 \stopsetups

    Appendices

115 \dodefinelettersection[\v!appendices]
116 \startsetups[letter:place:\v!appendices]
117 \dosetlettersection[\v!appendices]
118 \stopsetups

Fold- and cutmarks, you enable and disable all of them independant from any other or disable all marks with just one command.

119 \dodefineletterlayer[\v!foldmark]
120 \startsetups[letter:place:foldmark]
121 % Upper foldmark
122 \startlocalsetups[letter:place:topmark]
123 \dosetletterlayer[\v!topmark]
124 \stoplocalsetups
125 % Lower foldmark
126 \startlocalsetups[letter:place:botmark]
127 \dosetletterlayer[\v!botmark]
128 \stoplocalsetups
129 % Cutmark
130 \startlocalsetups[letter:place:cutmark]

```

```

131   \dosetletterlayer[\v!cutmark]
132   \stoplocalsetups
133   % Endmark, a relict from the typewriter area
134   \startlocalsetups[letter:place:endmark]
135   \dosetletterlayer[\v!endmark]
136   \stoplocalsetups
137   % Free mark, you could use it to place your own symbols
138   \startlocalsetups[letter:place:usermark]
139   \dosetletterlayer[\v!usermark]
140   \stoplocalsetups
141   \doif\cccc@lsoptiontopmark \v!yes{\setup[letter:place:topmark]}
142   \doif\cccc@lsoptionbotmark \v!yes{\setup[letter:place:botmark]}
143   \doif\cccc@lsoptioncutmark \v!yes{\setup[letter:place:cutmark]}
144   \doif\cccc@lsoptionendmark \v!yes{\setup[letter:place:endmark]}
145   \doif\cccc@lsoptionusermark\v!yes{\setup[letter:place:usermark]}

146 \stopsetups

```

Background graphic:

```

143 \defineoverlay
  [\v!graphic] % choose a better name!
  [\doifsomething\cccc@lsoptionbackgroundimage
    {\overlayfigure{\cccc@lsoptionbackgroundimage}}]

144 \def\letter!list!backgrounds
  {\v!color,\v!letternext,\v!lettermain,\v!head,\v!foot,%
   \v!backaddress,\v!graphic,\v!address,\v!reference,%
   \v!topmark,\v!botmark,\v!cutmark,\v!endmark,\v!usermark}

```

Settings at the begin of every letter.

```

145 \startsetups[letter:initialize]
146   \cccc@lsoptionbefore
147   \setupsubpagenumber
     [\c!number=\cccc@lsoptionpagenumber,
      \c!way=\v!by\v!text,
      \c!state=\cccc@lsoptionstate]
148   \resetsubpagenumber
149   \begingroup

```

```

150  \page
151  \setuppagenumbering
      [\c!alternative=\@@@@lsoptionalternative,
       \c!location=] % use the header and footer option instead
152  \the\letter!toks!header
      \the\letter!toks!footer
153  \setupbackgrounds
      [\v!page]
      [\c!background=\letter!list!backgrounds,
       \c!backgroundcolor=\@@@@lsoptionbackgroundcolor]
154  \doifsomething\@@@@lsoptionbodyfont{\switchtobodyfont[\@@@@lsoptionbodyfont]}
155  \doifsomething\@@@@lsoptionwhitespace{\setupwhitespace[\@@@@lsoptionwhitespace]}
156  \stopsetups

      Settings at the end of every letter.

157  \startsetups[letter:finish]
158  \page
159  \setuplayout[\v!reset]
160  \endgroup
161  \resetsubpagenumber
162  \@@@@lsoptionafter
163  \stopsetups

      Place the letter.

164  \startsetups[letter:place]
165  \setups[letter:initialize] % Settings at the begin
      \setups[letter:layout]     % Page layout
      \setups[letter:reset]      % Reset layers
      \setups[letter:layer]      % Place layers
      \setups[letter:sequence]   % Place content
      \setups[letter:finish]     % Settings at the end
166  \stopsetups

      Reset the layer content.

167  \def\letter!list!layers
      {\v!topmark,\v!botmark,\v!cutmark,\v!endmark,\v!usermark,\v!letternext,\v!lettermain}
168  \def\doresetletterlayer#1%
      {\resetlayer[#1]}

```

```

169 \startsetups[letter:reset]
170   \processcommacommmand[\letter!list!layers]\doresetletterlayer
171   \setuplayer[\v!letternext] [\c!state=\v!continue]
172 \stopsetups
173 \startsetups[letter:layer]
174   \doif\ccccclsoptionmarking \v!yes{\setups[letter:place:foldmark]}
   \doif\ccccclsoptionhead \v!yes{\setups[letter:place:head]}
   \doif\ccccclsoptionbackaddress\v!yes{\setups[letter:place:backaddress]}
   \doif\ccccclsoptionaddress \v!yes{\setups[letter:place:address]}
   \doif\ccccclsoptionreference \v!yes{\setups[letter:place:reference]}
   \doif\ccccclsoptionfoot \v!yes{\setups[letter:place:foot]}
   \doif\ccccclsoptionlettermain \v!yes{\setups[letter:place:lettermain]}
   \doif\ccccclsoptionletternext \v!yes{\setups[letter:place:letternext]}
175 \stopsetups

```

Place the letter content.

```

176 \let\letter!order!sections\letter!list!sections
177 \def\doflushlettersection#1%
  {\setups[letter:place:#1]}
178 \startsetups[letter:sequence]
179   \executeifdefined{\v!letter\s!start\c!optimize\ccccclsoptionoptimize}\donothing
   \processcommacommmand[\letter!order!sections]\doflushlettersection
   \executeifdefined{\v!letter\s!stop \c!optimize\ccccclsoptionoptimize}\donothing
180 \stopsetups

```

Framework for Letters

Default values

Default settings for the option values of the letter.

```

181  \setupletterstyle
      [\v!option]
      [\c!marking=\v!yes,
       \c!endmark=\v!no,
       \c!usermark=\v!no,
       \c!backaddress=\v!no,
       \c!indenting=,
       \c!whitespace=,
       \c!backgroundcolor=\v!white,
       \c!backgroundimage=,
       \c!before=,
       \c!after=,
       \c!header=\v!reset,
       \c!footer=\v!reset,
       \c!pagenumber=1,
       \c!bodyfont=,
       \c!optimize=\v!no,
       \c!alternative=\v!singled sided,
       \c!state=\v!stop]

182  \useletterinterface[\currentmoduleparameter\c!interface]
      \useletterstyle   [\currentmoduleparameter\c!style]
      \useletterextension[\currentmoduleparameter\c!extension]

183  \stopmodule

184  \protect \endinput

```

Framework for Letters

```
\letterstylevalue 9          \useletterextension 7  
\lettervalue 9           \useletterinterface 7  
                          \useletterstyle 7  
\setupletter 4  
\setupletterstyle 3
```